ALTV2416300ULCBM
AC CCTV Power Supply

Rev. DSALTV2416300ULCBM_10242012

ALTV2416300ULCBM

Overview

ALTV2416300ULCBM provides 24VAC or 28VAC distributed via Sixteen (16) Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:
- 115VAC, 50/60Hz, 2.7 amp.

Output:
- Sixteen (16) Class 2 Rated PTC protected power limited outputs.
- 24VAC @ 12.5 amp (300VA) supply current *(0.781 amp per device, 2.5 amp max.)* or 28VAC @ 10 amp (280VA) supply current *(0.625 amp per device, 2.5 amp max.)*.
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:
- Operating temperature: 0º C to 49º C ambient.
- BTU/Hr.:
  - 24VAC: 153.55 BTU/Hr.
  - 28VAC: 143.31 BTU/Hr.

Electrical *(cont'd)*:
- System AC input VA requirement: 310.5VA.

Features:
- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.

Mechanical:
- Enclosure Dimensions (H x W x D approx.): 8.5" (216mm) x 7.5" (191mm) x 3.5" (89mm)
- Product weight (approx.): 8.2 Lbs (3.719 kg)
- Shipping weight (approx.): 9.2 Lbs (4.173 kg)

Agency Approvals

UL Listed for Commercial CCTV Equipment (UL 2044).

CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

European Conformity

Enclosure Dimensions

8.5” (216mm) x 7.5” (191mm) x 3.5” (89mm)